



PRODUCT OVERVIEW

The TEAC W-865R/TAS is a simple, cost effective solution to installations which offers an impressive variety of playback and record options. Both decks have Dolby B noise reduction. Dual auto-reverse with Synchro reverse dubbing.



MSRP \$329.00

Twin IC logic control mechanisms

Dual auto-reverse tape transports

Variable pitch control +/- 10% (Deck 1)

Bi-directional double-deck continuous

Record/Playback.

Parallel recording (Decks 1 & 2 simultaneously)

Normal and High speed dubbing

Mic/Line mixing recording (Decks 1 & 2)

Microphone input with level control

Headphone output

Dolby B Noise Reduction

Left & Right peak program level meters

Dual 4-digit electronic tape counters

REC mute with auto spacer (Deck 2)

CPS Computomatic Program Search (Deck 1 & 2)

Intro Check and Blank Scan Functions

Auto tape type selector

Multi-Function fluorescent display

Optional Rack Mount Kit (TBA)

SPECIFICATIONS

Heads: Deck1: 1 Erase and 1

Record/Playback (rotating)
Deck 2: 1 Erase and 1
Record/Playback (rotating)

Motor: 2 DC Servo motors (1ea. Deck)

Wow & Flutter: 0.09% (WRMS)

Frequency Response: 25 - 19,000 Hz (Metal)
25 - 18,000 Hz (CrO2)
25 - 17,000 Hz (Normal)

Signal-to-Noise Ratio: 59 dB (NR off, 3% THD level,

Weighted)

69 dB (Dolby B NR on, over

5kHz)

79 dB (Dolby C NR on, over

1kHz)

Power requirements: 120/230V AC, 50/60 Hz Optional EIA rack mount kit available (RM-860) Optional remote control available (RC-544)

Dimensions: 17 1/8" x 4 15/16" x 11 1/2"

Weight: 8 13/16lbs (4 kg) **UPC#:** 0 43774 01023

